



MicroQR 2

The Future-Proof QR Code Reader
for Access Control and Visitor
Management

MicroQR 2

The Future-Proof QR Code Reader for Access Control and Visitor Management

Features



Versatile Interfaces

Equipped with Weigand 26/34, RS 485, RS232, and USB Virtual Serial Port interfaces, ensuring compatibility with your existing systems.



Lightning-Fast Reading

Achieve swift and precise data capture with a reading speed of under 200 ms, enhancing operational efficiency.



Wide QR Range

Capture QR codes effortlessly within a range of 0-20 cm, guaranteeing accurate identification every time.



Durable Construction

Crafted with a robust polycarbonate body and tempered metal glass, reinforced with an IP67 waterproof rating, ensuring durability in any environment.



Enhanced Security

Compatible with EM and MiFARE cards, providing seamless integration into your security protocols for heightened protection.



Sleek Design

Available in two timeless colors - Black and White, blending seamlessly with any aesthetic.

Specification

Interfaces	Wiegand 26/34, RS485, Rs232
Decoding	One dimensional QR code
Voltage	4 - 15V voltage input, 800mA
Directions	Camera centric slant 45°
Speed	<200 ms
QR Range	0 - 20 CM
Feature	Auto-induction, Beep control
Light source	LED light, anti-highlight interference
Decode	Image decoding
Environment	Temp.: -20~70°C, RH :10~90%
Material	PC body with tempered glass
Status Light	Red : Work, Green : Feedback
Card type	EM or Mifare (CSN) card
Reading Range	3 - 6 CM
USB	USB virtual Serial port
Size	86*86*42 (mm)
Environment	IP67 Waterproof

Ordering Information

- R100A-EM : for Proximity card based QR Reader
- R100A-MF : for Mifare card based QR Reader



Fortuna Impex Pvt Ltd

P-73, Kasba Industrial Estate, Phase-2, Kolkata - 700 107

☎ : +91 7550 670 670

✉ : info@fortunaindia.com

🌐 : www.fortunaimpex.com