

# VF 2000

AI based 7" Industrial grade (IP65 rated) Attendance & Access control Terminal with Mask, Temperature Logging\*



**Walk through by authenticating Face with Mask and Body Temperature\***

## Features



10,000 Face users  
(Upgradable to 25,000 users)



Cloud Compatible  
with Push Technology



Face Recognition  
with Mask



Face Enrollment using  
Device & Mobile App



Face Identification  
speed <0.3 sec. with  
spoof detection



Compatible to all  
Access Control Panel



Optional Temperature  
Detection & Logging



Ideal for outdoor Use for  
Access & Attendance

VF 2000 is Classic tall design with large screen 7" size with touch screen. It is weather proof, suitable for Access Control & Time Attendance features with Touchless AI/DL Face recognition technology.



VF 2000 is an elite model of our visible light face recognition product line. It adopts a deep learning algorithm to enable superior face recognition performance, providing an excellent user experience. Equipped with an industrial IPS touchscreen and a metal casing with an IP65 design, it allows broad deployment in schools, hospitals, central buildings, offices, and stores for access control and time attendance.

### VF 2000 : Face Recognition based Attendance System with Mask detection with Body temperature\*

User Capacity	Standard 10,000 Face (1:N), upgradable to 25,000 Face (1:N)
Speed	Less than 0.3 Second
Accuracy	>99%
Lighting compatible	0.1 Lux ~ 30,000 Lux
Working Distance	0.3 - 2 meter
Record Capacity	2,00,000
Security Photo	2,00,000
Card Reader	EM Proximity Reader (Optional MIFARE Reader )
Authentication	Face, Card+Face, Card/Face, ID+Pin
Mask Detection	Yes
Temperature Detection*	Distance: 30cm~50cm (1ft~1.64ft), Range: 33°C~42°C(91.4°F~107.6°F) Accuracy: +/-0.3°C ( +/-32.54°F), indoor without wind
Attendance	Interval, Work Status, Work Code
Operating System	Linux 4.9
Processor	Dual-core 1GHZ
Screen	Industry 7 inch Touch Screen, Resolution 1200 X 800 Pixel
Sensor	Dual Camera with 1080P/30fps
Storage	EMMC FLASH 8Gbytes, 16GB TF
Interface	Wifi, TCP/IP, USB, RS485, Weigand Output, Relay, Exit Door
Working Environment	For terminal: -20°C~70°C(-4°F~158°F), Humidity <95%(non Condensing) Temperature module: 10°C~40°C(50°F~104°F)
Power	DC 12V 2A
Dimension	230*25*120 mm
Weight	0.85 Kg (Metal Casing)
Mounting	Wall Mounting, Turnstile Mounting

\*Specifications are subject to change without notice

#### Communication Platform Software & API's

- **Smart Face** : Web Based Communication Server for Face & Finger Terminal, Template & Data Management with Push Technology
- **PM Neo** : API integration project with HRMS/Payroll/ERP software for Employee Master, Templates, Terminal & Transaction data

#### T & A Application Software

- **Smart Face Attendance** : Web based Platform Software with Built-in Attendance Management & Leave Module
- **eZeeHR** : Progressive HRMS Suite with Attendance, Shift, Leave, HR Module
- **OTG HR** : Cloud based Attendance System(including Mobile App) with Intra-office Task Management Solution

#### Ordering Information

- **VF 2000** : 7" Wall mounting Device
- **VF 2000B** : 7" Turnstile mounting Device
- **VF 2000T** : 7" Wall mounting Device with Temperature Sensor
- **VF 2000BT** : 7" Turnstile mounting Device with Temperature Sensor

#### Options

- **OPT 02** : Upgrade to 25,000 Face users
- **OPT 04** : Built in Mifare Reader
- **OPT 06** : Battery Back-up (2Hrs) for VF 2000
- **OPT 07** : Panel for VF 2000



☎ : +91 7550 670 670  
+91 733 000 4448

✉ : [info@fortunaindia.com](mailto:info@fortunaindia.com)  
🌐 : [www.fortunaindia.com](http://www.fortunaindia.com)